

SuperV drills

Application recommendations

Feed column										
Code-letter	A	B	C	D	E	F	G	H	I	
drill-Ø mm	0,50	0,004	0,006	0,007	0,008	0,010	0,012	0,014	0,016	0,019
	1,00	0,006	0,008	0,012	0,014	0,016	0,018	0,020	0,023	0,025
	2,00	0,020	0,025	0,032	0,040	0,050	0,063	0,080	0,100	0,125
	2,50	0,025	0,032	0,040	0,050	0,063	0,080	0,100	0,125	0,160
	3,15	0,032	0,040	0,050	0,063	0,080	0,100	0,125	0,160	0,160
	4,00	0,040	0,050	0,063	0,080	0,100	0,125	0,160	0,200	0,200
	5,00	0,040	0,050	0,063	0,080	0,100	0,125	0,160	0,200	0,250
	6,30	0,050	0,063	0,080	0,100	0,125	0,160	0,200	0,250	0,315
	8,00	0,063	0,080	0,100	0,125	0,160	0,200	0,250	0,315	0,315
	10,00	0,080	0,100	0,125	0,160	0,200	0,250	0,315	0,400	0,400
	12,50	0,080	0,100	0,125	0,160	0,200	0,250	0,315	0,400	0,500
	16,00	0,100	0,125	0,160	0,200	0,250	0,315	0,400	0,500	0,630
	20,00	0,125	0,160	0,200	0,250	0,315	0,400	0,500	0,630	0,630
	25,00	0,160	0,200	0,250	0,315	0,400	0,500	0,630	0,800	0,800
	31,50	0,160	0,200	0,250	0,315	0,400	0,500	0,630	0,800	1,000
	40,00	0,200	0,250	0,315	0,400	0,500	0,630	0,800	1,000	1,250

Tools with feed column no. in bold are preferred choices for listed material group.

K, P, K/P

Since our new carbide grades are universally applicable we now define our carbide application groups as K or K/P only.

Meaning of code letters with type descriptions:

- G** for cast iron, AlSi-alloys
- S** for high-tensile materials
- U/F** for universal machining, carbon steels
- VA** for stainless materials
- UX** for the machining of steel
- * apply heavily tapered tools

Lubricants:

- cutting oil, highly activated
- soluble oil (emulsion)
- without lubricant
- air only

Material group	Materials examples, new designations (old designation in brackets) Figures in bold = material no. to DIN EN	Tensile strength MPa (N/mm ²)	Hardness	Coolant
General purpose steels	1.0035 S185(St33), 1.0486 P275N(StE285), 1.0345 P235GH(H1), 1.0425 P265GH(H2) 1.0050 E295 (St50-2), 1.0070 E360 (St70-2), 1.8937 P500NH (WStE500)	≤500 >500-850		<input checked="" type="checkbox"/>
Free-cutting steels	1.0718 11SMnPb30 (9SMnPb28), 1.0736 11SMn37 (9SMn36) 1.0727 46S20 (45S20), 1.0728 (60S20), 1.0757 46SPb20 (45SPb20)	≤850 850-1000		<input checked="" type="checkbox"/>
Unalloyed tempering steels	1.0402 C22, 1.1178 C30E (Ck30) 1.0503 C45, 1.1191 C45E (Ck45) 1.0601 C60, 1.1221 C60E (Ck60)	≤ 700 700-850 850-1000		<input checked="" type="checkbox"/>
Alloyed tempering steels	1.5131 50MnSi4, 1.7003 38Cr2, 1.7030 28Cr4 1.5710 36NiCr6, 1.7035 41Cr4, 1.7225 42CrMo4	850-≤1000 1000-1200		<input checked="" type="checkbox"/>
Unalloyed case hardened steels	1.0301 (C10), 1.1121 C10E (Ck10)	≤750		<input checked="" type="checkbox"/>
Alloyed case hardened steels	1.7043 38Cr4 1.5752 15NiCr13 (15NiCr13), 1.7131 16MnCr5, 1.7264 20CrMo5	850-≤1000 1000-1200		<input checked="" type="checkbox"/>
Nitriding steels	1.8504 34CrAl6 1.8519 31CrMoV9, 1.8550 34CrAlNi7	≥850-≤1000 >1000-1200		<input checked="" type="checkbox"/>
Tool steels	1.1750 C75W, 1.2067 102Cr6, 1.2307 29CrMoV9 1.2080 X210Cr12, 1.2083 X42Cr13, 1.2419 105WCr6, 1.2767 X45NiCrMo4	≤850 >850-1000		<input checked="" type="checkbox"/>
High speed steels	1.3243 S 6-5-2-5, 1.3343 S 6-5-2, 1.3344 S 6-5-3	≥650-1000		<input checked="" type="checkbox"/>
Spring steels	1.5026 55Si7, 1.7176 55Cr3, 1.8159 51CrV4 (51CrV4)		≤330 HB	<input checked="" type="checkbox"/>
Hardened steels	-		≤40-48 HRC >48-60 HRC	<input checked="" type="checkbox"/>
Stainless steels, sulphured austenitic martensitic	1.4005 X12CrS13, 1.4104 X14CrMoS17, 1.4105 X6CrMoS17, 1.4305 X8CrNiS18-9 1.4301 X5CrNi18-10 (V2A), 1.4541 X6CrNiTi18-10, 1.4571 X6CrNiMoTi 17-12-2 (V4A) 1.4057 X20CrNi 17 2 (X17CrNi16-2), 1.4122 X39CrMo17-1, 1.4521 X2CrMoTi18-2	≤850 ≤850 ≤850		<input checked="" type="checkbox"/>
Cast iron	0.6010 EN-GJL-100(GG10), 0.6020 EN-GJL-200(GG20) 0.6025 EN-GJL-250(GG25), 0.6035 EN-GJL-350(GG35)	850-≤1000 1000-1200		<input checked="" type="checkbox"/>
Spheroidal graphite iron and malleable cast iron	0.7050 EN-GJS-500-7(GGG50), 0.8035 EN-GJMw-350-4(GTW35) 0.7070 EN-GJS-700-2(GGG70), 0.8170 EN-GJMB-700-2(GTS70)		≤240 HB <300 HB	<input checked="" type="checkbox"/>
Chilled cast iron	-		≤350 HB	<input checked="" type="checkbox"/>
New Cast iron GGV	EN-GJV250 (GGV25), EN-GJV350 (GGV35) EN-GJV400 (GGV40), EN-GJV500 (GGV50), SiMo6			<input checked="" type="checkbox"/>
New Cast iron ADI	EN-GJS-800-8 (ADI800), EN-GJS-1000-5 (ADI1000) EN-GJS-1200-2 (ADI1200), EN-GJS-1400-1 (ADI1400)	800-1000 1200-1400		<input checked="" type="checkbox"/>
Special alloys	Nimonic, Inconel, Monel, Hastelloy	≤1200		<input checked="" type="checkbox"/>
Ti and Ti-alloys	3.7024 Ti99,5, 3.7114 TiAl5Sn2,5, 3.7124 TiCu2 3.7154 TiAl6Zr5, 3.7165 TiAl6V4, 3.7184 TiAl4Mo4Sn2,5, - TiAl8Mo1V1	≤850 >850-1200		<input checked="" type="checkbox"/>
Aluminium and Al-alloys	3.0255 Al99,5, 3.2315 AlMgSi1, 3.3515 AlMg1	≤400		<input checked="" type="checkbox"/>
Al wrought alloys	3.0615 AlMgSiPb, 3.1325 AlCuMg1, 3.3245 AlMg3Si, 3.4365 AlZnMgCu1,5	≤450		<input checked="" type="checkbox"/>
Al cast alloys ≤ 10 % Si > 10 % Si	3.2131 G-AlSi5Cu1, 3.2153 G-AlSi7Cu3, 3.2573 G-AlSi9 3.2581 G-AlSi12, 3.2583 G-AlSi12Cu, - G-AlSi12CuNiMg	≤600 ≤600		<input checked="" type="checkbox"/>
Magnesium alloys	3.5200 MgMn2, 3.5812.05 G-MgAl8Zn1, 3.5612.05 G-MgAl6Zn1	≤450		<input type="checkbox"/>
Copper, low alloyed	2.0070 SE-Cu, 2.1020 CuSn6, 2.1096 G-CuSn5ZnPb	≤400		<input checked="" type="checkbox"/>
Brass, short-chipping long-chipping	2.0380 CuZn39Pb2, 2.0401 CuZn39Pb3, 2.0410 CuZn43Pb2 2.0250 CuZn20, 2.0280 CuZn33, 2.0332 CuZn37Pb0,5	≤600 ≤600		<input checked="" type="checkbox"/>
Bronze, short-chipping	2.1090 CuSn7ZnPb, 2.1170 CuPb5Sn5, 2.1176 CuPb10Sn 2.0790 CuNi18Zn19Pb	≤600 >600-850		<input checked="" type="checkbox"/>
Bronze, long-chipping	2.0916 CuAl5, 2.0960 CuAl9Mn, 2.1050 CuSn10 2.0980 CuAl11Ni, 2.1247 CuBe2	≤850 >850-1000		<input checked="" type="checkbox"/>
Duroplastics	Epoxidharz, Resopal, Pertinax, Moltopren			<input type="checkbox"/>
Thermoplastics	Plexiglas, Hostalen, Novodur, Makralon			<input checked="" type="checkbox"/>
Kevlar	Kevlar			<input type="checkbox"/>
Glass/carbon-concentr. plastics	GFK/CFK			<input type="checkbox"/>

≤5×D drilling depth

Catalog no.	51681	51781	51881	51754	51755	51772	51773	51785	71862
Tool material	VHM	VHM	VHM	VHM	VHM	VHM	VHM	VHM	VHM
Carbide grade	K/P	K/P	K/P	K/P	K/P	K/P	K/P	K/P	K
Surface finish	TiAlN nano	TiAlN nano	TiAlN nano	TiAlSiN	TiAlSiN	AlTiN nano	AlTiN nano	TiAlN nano	bright
DIN/Form	6537L	6537L	6537L	6537L	6537L	6537L	6537L	6537L	6537L
Type	U	U	U	S	S	VA	VA	UX	V83-GAL
Coolant	with	with	with	with	with	with	with	with	without
Page	36	32	34	65	67	76	78	57	80



V _c m/min	Feed no.			V _c m/min	Feed no.			V _c m/min	Feed no.			V _c m/min	Feed no.		
145	G	G	G	145	G	G		145-230	H						
120	F	F	F	120	F	F		120-220	G						
170	H	H	H	170	H	H		170-260	H						
145	H	H	H	145	H	H		145-230	H						
130	H	H	H	130	H	H		130-220	H						
125	G	G	G	125	G	G		125-210	G						
120	G	G	G	120	G	G		120-200	G						
120	G	G	G	120	G	G		120-210	G						
105	G	G	G	105	G	G		105-200	G						
145	H	H	H	145	H	H		145-230	H						
120	G	G	G	120	G	G		120-210	G						
85	E	E	E	85	E	E		105-200	F						
105	G	G	G	110	G	G		110-150	G						
100	E	E	E	105	E	E		100-150	E						
70	F	F	F	80	F	F		70-120	F						
55	E	E	E	65	E	E		55-100	E						
60	E	E	E	60	D	D		60-100	E						
60	C	C	C	60	C	C		60-100	E						
55	C	C	C	55	C	C									
35	B	B	B	35	B	B									
60	E	E	E				80	E	E						
55	B	B	B				60	B-C	B-C						
50	E	E	E				80	E	E						
195	I	I	I									100	F		
160	I	I	I									80	F		
140	I	I	I									80	F		
130	H	H	H									70	F		
40	C	C	C												
35	D	D	D	35	D	D	30	D	D						
45	D	D	D	45	D	D	45	D	D						
40	C	C	C	40	C	C	40	C	C						
310	I	I	I									180	G		
310	I	I	I									160	G		
260	I	I	I									150	G		
220	I	I	I									120	F		
280	H	H	H									180	F		
125	G	G	G												
325	H	H	H									180	F		
220	G	G	G												
125	G	G	G												
105	F	F	F												
90	F	F	F												
80	F	F	F												